

# LEED® INFORMATION BROCHURE

## STONSHIELD SLT

# STONSHIELD

Stonshield SLT is a seamless, free flowing flooring system engineered with a textured surface for slip resistance in commercial and industrial applications. This 2 or 3 mm flooring system provides a cost effective alternative to Stonshield HRI for light traffic applications. It is ideally suited for use in light manufacturing areas, correctional institutions, research, hospitals, health-care, recreational and educational facilities.

Stonhard, the leader in seamless polymer floors, walls and linings, works with customers and within our own organization to provide more "green" products to the marketplace. As the Global Leader, we have numerous manufacturing facilities that can be utilized to deliver locally manufactured materials to your project. We have developed a unique packaging method that eliminates 85% of the normal waste by volume associated with metal cans from conventional polymer flooring. Combine our packaging, our complete line of low emitting products with our unique polymer floor systems, which incorporate recycled aggregate materials, and it's clear that we are committed to providing the products and initiatives to help you gain LEED® certification. Together, we can lessen our impact on the environment - Stonhard will help your project go Green!



Tim McCulloch  
Engineering / Tech Support Manager  
Stonhard division, RPM Canada

### Indoor Environmental Quality (EQ) Credit 4.2 - Low-Emitting Materials

<u>Stonshield SLT</u>	<u>VOC</u> (g/L)	<u>Volume</u> (L)
Standard Primer	5	3
Stonshield Undercoat	5	20
Stonshield Aggregate	0	45
Stonshield Sealer	5	16

Total Weighted VOC Per System - 2 g/L

Total Volume Per System - 84 L

### Materials & Resources (MR) Credit 5 - Regional Materials

<u>Manufacturing Location:</u>	<u>Shipping Method:</u>
One Park Avenue Maple Shade, NJ	Truck: _____ km
<u>Material Cost:</u>	<u>Total Project Sq. Ft.:</u>
\$ _____ / sq. ft.	_____

