

Date Revised: 06/07/2018

Supersedes: 06/16/2017

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION		
Product Name(s):	Five Star Structural Concrete [®] HTR Shotcrete	
Synonyms:	Shotcrete, Gunite	
Product Use:	Dry process shotcrete application for general construction and concrete repair for high temperature environments.	
Restrictions on Use:	Use per Five Star's product recommendation	
Manufacturer/Supplier	Five Star Products, Inc. 60 Parrott Drive Shelton, CT 06484 USA	
Phone #:	203-336-7900	
Emergency Phone #:	CHEM-TEL 1-800-255-3924 (Outside the U.S. 1-813-248-0585)	
SECTION 2: HAZARD(S) IDE	NTIFICATION-GHS INFORMATION	
Classification:	Acute Oral Toxicity – Category 4 Skin Corrosion/Irritation – Category 1 Acute Toxicity – Dermal, Category 5 Sensitization – Dermal, Category 1 Eye Damage/Irritation – Category 1 Sensitization – Respiratory, Category 1 Specific Target Organ Systemic Toxicity (Single Exposure) – Cat 3 Carcinogenicity – Category 1A Specific Target Organ Toxicity (Repeated Exposure) – Cat 2	
	Acute Oral Toxicity – Category 4 Skin Corrosion/Irritation – Category 1 Acute Toxicity – Dermal, Category 5 Sensitization – Dermal, Category 1 Eye Damage/Irritation – Category 1 Sensitization – Respiratory, Category 1 Specific Target Organ Systemic Toxicity (Single Exposure) – Cat 3 Carcinogenicity – Category 1A	

Hazard Statements:

H302 Harmful if swallowed H313 May be harmful in contact with skin H314 Causes severe skin burns and eye damage H317 May cause an allergic skin reaction H318 Causes serious eye damage H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled H335 May cause respiratory irritation H350 May cause cancer



Date Revised: 06/07/2018

Supersedes: 06/16/2017

H373 May cause damage to organs through prolonged or repeated

	exposure
Precautionary Statements/Prevention:	 P260 Do not breathe dust, fume, gas, mist, vapors, or spray. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves, protective clothing, eye protection and face protection. P284 Wear respiratory protection.
Response:	 P330, P331 If swallowed: Rinse mouth. Do NOT induce vomiting. P361, P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P351 If in eyes: Rinse cautiously with water for several minutes. P338 Remove contact lenses, if present and easy to do. Continue rinsing. P330 If skin irritation or rash occurs: P313 Get medical advice / attention. P342 If experiencing respiratory symptoms: P310 Call a poison center or doctor.
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.
Hazards Not Otherwise Classified:	Not Applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt∕wt
Hydraulic Cement	Not Applicable	65997-16-2	30-35
Quartz	Silicon Dioxide, Silica Sand	14808-60-7	65-70

SECTION 4: FIRST AID MEASURES

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms call poison center or doctor.

FIVE STAR	Safety Data Sheet	Date Revised:	06/07/2018
	Salety Data Sheet	Supersedes:	06/16/2017
Eye Contact:	If in eyes: Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.		
Skin Contact:	If on skin (or hair): Take off immedia skin with water/shower for at least 15 center or doctor if irritation deve before reuse.	5 minutes. Imme	ediately call a poison
Ingestion:	If swallowed: Rinse mouth. Do NOT poison center or doctor. If vomiting forward to reduce the risk of aspirat to an unconscious person.	occurs naturall	y, have victim lean
General Advice:	In case of accident or if you feel unwe (show the label or SDS where possib		advice immediately
Note to Physicians:	Symptoms may not appear immedia	tely. Treat symp	otomatically.

SECTION 5: FIRE-FIGHTING MEASURES		
Flammability and Explosion Information:	Not flammable or combustible by OSHA/WHMIS criteria.	
Sensitivity to Mechanical Impact:	This material is not sensitive to mechanical impact.	
Sensitivity to Static Discharge:	This material is sensitive to static discharge at temperatures at or above the flash point.	
MEANS OF EXTINCTION		
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, or water spray. Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire- control water for later disposal; do not scatter the material.	
Unsuitable Extinguishing Media:	Not available	
Product of Combustion:	Non-combustible	
Protection of Firefighters:	As in any fire, wear self-contained breathing apparatus pressure- demand, MSHA/NIOSH (approved or equivalent) and full protective gear.	

SECTION 6: ACCIDENTAL RELEASE MEASURES	
Emergency Procedures:	Use personal protective equipment. Ensure adequate ventilation. Keep people from spill. Avoid dust formation.
Personal Precautions:	Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.



Date Revised: 06/07/2018

Supersedes: 06/16/2017

Environmental Precautions:	The environmental impact of this product has not been fully investigated.
Methods for Containment:	Cover powder spill with plastic sheet or tarp to minimize spreading. Collect this material into a disposal container by sucking or sweeping up.
Methods for Cleanup:	Pick up and transfer to properly labeled containers.
Other Information:	See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE	
Handling:	Wear personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Do not breathe dust. Prevent contact with skin, eyes, and clothing. Wash thoroughly after handling.
Storage:	Keep containers tightly closed in a cool, dry, and well-ventilated place. Store locked up.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	CAS No.	ACGIH TLV	OSHA PEL
Hydraulic Cement	65997-16-2	TWA: 1mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf; <1% Crystalline silica
Quartz**	14808-60-7	TWA: 0.025mg/m ³ respirable fraction	TWA: 0.050 mg/m ³ AL: 0.025 mg/m ³

PEL: Permissible Exposure Limit TLV: Threshold Limit Value AL: Actionable Level

** Respirable(< 6 micron) fraction for product is < 0.1%.

Engineering Controls: Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

- Eye/Face Protection:Tightly fitting safety goggles
- Hand Protection: Impervious gloves. Impervious clothing.
- Skin and Body Protection: Impervious gloves. Impervious clothing.
- **Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



Supersedes: 06/16/2017

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Finely ground solid powder	
Color:	Tan to Gray	
Odor:	None	
Odor Threshold:	None	
Physical State:	Solid, powder	
pH:	12 when mixed with water	
Melting Point / Freezing Point:	1,832°F (1,000°C)	
Initial Boiling Point:	Not Available	
Boiling Point:	> 3,632°F (2,000°C)	
Flash Point:	Not Applicable	
Evaporation Rate:	Not Applicable	
Flammability (solid, gas):	Not Applicable	
Lower Flammability Limit:	Not Applicable	
Upper Flammability Limit:	Not Applicable	
Vapor Pressure:	Not Applicable	
Vapor Density:	Not Applicable	
Relative Density:	2.7 – 3.1	
Solubility:	Slight 0.2-0.5%	
Partition Coefficient: n-Octanol/Water:	Not Applicable	
Auto-ignition Temperature:	Not Applicable	
Decomposition Temperature:	Not Available	
Viscosity:	Not Applicable	
Percent Volatile, wt.%:	0	
VOC Content, wt.%:	0	
Density:	2.7 – 3.1 g/cc	
Coefficient of Water/Oil Distribution:	Not Applicable	



Date Revised: 06/07/2018

Supersedes: 06/16/2017

SECTION 10: STABILITY AND REACTIVITY		
Chemical Stability:	Stable under recommended storage conditions.	
Possibility of Hazardous Reactions:	None under normal processing.	
Conditions to Avoid:	Exposure to water – product may harden on contact with water.	
Incompatible Materials:	Strong acids.	

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product information

Ingestion:

Inhalation:	Irritating to respiratory system. Irritating to mucous membranes.
Eye contact:	Risk of serious damage to eyes.
Skin contact:	Irritating to skin. May cause allergic skin reaction. May cause alkali burns.

Harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Hydraulic Cement	Not Available	Not Available	Not Available	

Secondary Component Information:

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Quartz	500 – 22,500 mg/kg (Rat)	Not Established	Not Established*	

*LCL50: 0.3 mg/m3 / 10Y (Human)

Symptoms related to the physical, chemical and toxicological characteristics:

No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization:	May cause sensitization by skin contact.	
Mutagenic Effects:	No information available.	
Carcinogenicity:	The table below indicates whether each agency has listed any ingredient as a carcinogen. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). May cause cancer by inhalation.	

Chemical Name	ACGIH	IARC	ΝΤΡ	OSHA	
Quartz	A2*	Group 1	Known	х	

*The respirable fraction as a whole is less than 0.1% and anticipated usage would generate far less than 0.1% as a respirable quantity above exposure guidelines as noted in Section 8.



Supersedes: 06/16/2017

ACGIH: (American Conference of Governmental Industrial Hygienists):	A2 - Suspected Human Carcinogen
IARC: (International Agency for Research on Cancer):	Group 1 - Carcinogenic to Humans
NTP: (National Toxicity Program):	Known Carcinogen
OSHA: (Occupational Safety & Health Administration):	X - Present
Reproductive Toxicity:	No information available.
STOT - single exposure:	May cause respiratory irritation.
STOT - repeated exposure:	Causes damage to organs through prolonged or repeated exposure if inhaled. Lungs.
Chronic Toxicity:	Inhalation overexposure to free crystalline silica may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease.
Aspiration Hazard:	No information available.
Numerical measures of toxicity	- Product
The following values are calculated based on chapter 3.1 of the GHS document:	LD 50 Oral: 500 mg/kg; Acute toxicity estimate

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:	The environmental impact of this product has not been fully investigated.	
Aquatic Toxicity:	The environmental impact of this product has not been fully investigated.	
Persistence and Degradability:	No information available.	
Bio-accumulative Potential:	Does not accumulate in organisms	
Mobility in Soil:	No further relevant information available	
Ecotoxical Effects Remark:	No information available.	
Additional Ecological Information:	No information available.	
General Notes:	This statement was deduced from products with a similar structure or composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Addition of water to cement creates an alkaline pH of between 12-13. Cured product is inert. Common to concrete construction around waterways, particular concern should be given to best practices to avoid/minimize	



Date Revised: 06/07/2018

Supersedes: 06/16/2017

spillage/discharge to the nearby environment as best as possible. In the case of significant spillage in confined or restricted areas, pH may increase to a level toxic to fish and aquatic organisms.

PBT Assessment:	Not Available
vPvB Assessment:	Not Available
Other Adverse Effects:	No further relevant information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation:	This material as supplied is not a hazardous waste according to Federal regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered.		
Uncleaned Packaging			
Recommendation:	Disposal must be made according to official regulations. Do not re-use empty containers.		

SECTION 14: TRANSPORT INFORMATION		
US DEPARTMENT of TRANSPORTATION (DOT)		
Proper Shipping Name:	Not Regulated	
Class:	Not Applicable	
UN #:	Not Applicable	
Packing Group:	Not Applicable	
CANADA Transportation of Dangerous Goods (TDG)		
Proper Shipping Name:	Not Regulated	
Class:	Not Applicable	
UN #:	Not Applicable	
Packing Group:	Not Applicable	
INTERNATIONAL AIR TRANSPORTATION Proper		
Shipping Name (ICAO/IATA):	Not Regulated	
Class:	Not Applicable	
UN#:	Not Applicable	
Packing Group:	Not Applicable	



WATER TRANSPORTATION Proper Shipping Name	
(IMO/IMDG):	Not Regulated
Class:	Not Applicable
UN #:	Not Applicable
Packing Group:	Not Applicable
Marine Pollutant:	Not Applicable

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES							
US (TSCA):	The components of this product are in compliance with the chemical notification requirements of TSCA.				chemical		
CANADA (DSL):	The component notification rec						
U.S. FEDERAL REGULATIONS	Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the CFR, Part 372.						
UNITED STATES:	This SDS has been prepared to meet the US OSHA Hazard Communication Standard, 29 CFR 1910.1200						
SARA 311/312 Hazard Categories	Chronic Health Fire Hazard – Sudden Releas	ite health hazard – Yes ionic Health hazard – Yes					
US STATE Right to Know Regulations	Chemical Name Hydraulic Cement Quartz	X X	MA X X	PA X X	IL	RI X X	_
California	This product contains the following Proposition 65 chemicals						

California California Prop 65: This product contains the following Proposition 65 chemicals. Chemical Name: Quartz CAS-No: 14808-60-7 CA Prop. 65: Carcinogen



Supersedes: 06/16/2017

SECTION 16: OTHER INFORMATION

HMIS Rating:

Health	Flammability Physical Hazard		Personal Protection	
1	0	1	E,X	

Disclaimer:

This information is furnished without warranty of any kind, expressed or implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and accurate.