# **Safety Data Sheet**

# Prepared in Accordance with HCS 29 C.F.R. 1910.1200



# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 6323/POL Revision Date: 10/25/2018

Base component of 2 components coating - Industrial use.

Product Name: GS6 SILVER GRAY POLYOL

Supercedes Date: 06/25/2018

1.2 Relevant identified uses of the substance or mixture and uses

advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

**1.4 Emergency telephone number:** CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside ÚS)

# 2. Hazard Identification

### 2.1 Classification of the substance or mixture

Carcinogenicity, category 1B Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1B

### 2.2 Label elements

# Symbol(s) of Product





# Signal Word

Danger

#### Named Chemicals on Label

Solvent naphtha (petroleum), light arom.

#### **HAZARD STATEMENTS**

| Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1B Carcinogenicity, category 1B PRECAUTION PHRASES | H226<br>H340-1B<br>H350-1B | Flammable liquid and vapour. May cause genetic defects. May cause cancer. |
|--|----------------------------|---|
|  | P201                       | Obtain special instructions before use.                                   |
|  | P202                       | Do not handle until all safety precautions have been read and understood. |
|  | P210                       | Keep away from heat, hot surfaces, sparks, open flames and                |

other ignition sources. No smoking.

P284 Wear respiratory protection.

P308+313 IF exposed or concerned: Get medical advice/attention. P403+233 Store in a well-ventilated place. Keep container tightly

closed.

### 2.3 Other hazards

No Information

# Results of PBT and vPvB assessment:

No information

# 3. Composition/Information On Ingredients

# 3.2 Mixtures

### **Hazardous Ingredients**

| <u>CAS-No.</u> | <u>Chemical Name</u>                     | <u>%</u>    |
|----------------|--|-------------|
| 13463-67-7     | titanium dioxide                         | 10 - <25    |
| 108-65-6       | 2-methoxy-1-methylethyl-acetate          | 2.5 - <10   |
| 763-69-9       | ethyl 3-ethoxypropionate                 | 2.5 - <10   |
| 112926-00-8    | hydrated, amorphous silica               | 1.0 - <2.5  |
| 123-54-6       | Pentane-2,4-dione                        | 1.0 - <2.5  |
| 7631-86-9      | silicon dioxide (amorphous)              | 1.0 - <2.5  |
| 108-83-8       | 2,6-dimethylheptan-4-one                 | 0.1 - <1.0  |
| 21645-51-2     | alumina trihydrate                       | 0.1 - <1.0  |
| 64742-95-6     | Solvent naphtha (petroleum), light arom. | 0.1 - <1.0  |
| 123-86-4       | n-butyl acetate                          | 0.1 - < 1.0 |

| CAS-No.     | GHS Symbols | GHS Hazard Statements | M-Factors |
|-------------|-------------|-----------------------|-----------|
| 13463-67-7  |             |                       | 0         |
| 108-65-6    | GHS02       | H226                  | 0         |
| 763-69-9    | GHS02-GHS07 | H226-335              | 0         |
| 112926-00-8 |             |                       | 0         |
| 123-54-6    | GHS02-GHS06 | H226-301-331          | 0         |
| 7631-86-9   |             |                       | 0         |
| 108-83-8    | GHS02-GHS06 | H226-331-335-336      | 0         |
| 21645-51-2  |             |                       | 0         |
| 64742-95-6  | GHS07-GHS08 | H304-335-336-340-350  | 0         |
| 123-86-4    | GHS02-GHS07 | H225-336              | 0         |

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

# 4. First-aid Measures

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** No Information

AFTER INHALATION: Move to fresh air. Keep respiratory tract clear.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything

by mouth to an unconscious person.

### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Harmful in contact with skin and if swallowed. May cause long-term adverse effects in the aquatic environment.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

Flammable.

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water mistDry powderFoamCarbon dioxide (CO2)High volume water jet. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions.

# 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

# 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# 7. Handling and Storage

## 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Electrical equipment should be protected to the appropriate standard. Use only in area provided with appropriate exhaust ventilation. Provide exhaust ventilation close to floor level. Wear personal protective equipment.

**PROTECTION AND HYGIENE MEASURES:** Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice for diagnostics.

#### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Direct sources of heat.

**STORAGE CONDITIONS:** Keep in an area equipped with solvent resistant flooring. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

| <u>Name</u>   | CAS-No.  | ACGIH TWA   | ACGIH STEL A | CGIH Ceiling |
|---|--|---|--------------|--------------|
| titanium dioxide  | 13463-67-7   | 10 MGM3 10 MGM3   |              |              |
| 2-methoxy-1-methylethyl-acetate   | 108-65-6   | 100 ppm   |              |              |
| ethyl 3-ethoxypropionate  | 763-69-9   |   |              |              |
| hydrated, amorphous silica  | 112926-00-8  | 10.00 MG/M3   |              |              |
| Pentane-2,4-dione   | 123-54-6   | 25 PPM  |              |              |
| silicon dioxide (amorphous)   | 7631-86-9  | 10.0 mg/m3  |              |              |
| 2,6-dimethylheptan-4-one  | 108-83-8   | 25 PPM  |              |              |
| alumina trihydrate  | 21645-51-2   | 10.0 mg/m3  |              |              |
| Solvent naphtha (petroleum), light arom.  | 64742-95-6   | 300.0 PPM   |              |              |
| n-butyl acetate   | 123-86-4   | 50 PPM  | 150 PPM      |              |
|   |  |   |              |              |
| Nama  | CAS-No   | OSHV DEI  | OCHA CTEI    |              |
| <u>Name</u>   | CAS-No.  | OSHA PEL  | OSHA STEL    |              |
| Name titanium dioxide   | <b>CAS-No.</b> 13463-67-7  | OSHA PEL<br>15.0 mg/m3                                    | OSHA STEL    |              |
|   |  |   | OSHA STEL    |              |
| titanium dioxide  | 13463-67-7   |   | OSHA STEL    |              |
| titanium dioxide  2-methoxy-1-methylethyl-acetate   | 13463-67-7<br>108-65-6   |   | OSHA STEL    |              |
| titanium dioxide  2-methoxy-1-methylethyl-acetate ethyl 3-ethoxypropionate  | 13463-67-7<br>108-65-6<br>763-69-9   | 15.0 mg/m3  | OSHA STEL    |              |
| titanium dioxide  2-methoxy-1-methylethyl-acetate ethyl 3-ethoxypropionate hydrated, amorphous silica   | 13463-67-7<br>108-65-6<br>763-69-9<br>112926-00-8                                      | 15.0 mg/m3  | OSHA STEL    |              |
| titanium dioxide  2-methoxy-1-methylethyl-acetate ethyl 3-ethoxypropionate hydrated, amorphous silica Pentane-2,4-dione   | 13463-67-7<br>108-65-6<br>763-69-9<br>112926-00-8<br>123-54-6                          | 15.0 mg/m3<br>6.00 MG/M3<br>0.8 mg/m3                     | OSHA STEL    |              |
| titanium dioxide  2-methoxy-1-methylethyl-acetate ethyl 3-ethoxypropionate hydrated, amorphous silica Pentane-2,4-dione silicon dioxide (amorphous)                           | 13463-67-7<br>108-65-6<br>763-69-9<br>112926-00-8<br>123-54-6<br>7631-86-9             | 15.0 mg/m3<br>6.00 MG/M3<br>0.8 mg/m3                     | OSHA STEL    |              |
| titanium dioxide  2-methoxy-1-methylethyl-acetate ethyl 3-ethoxypropionate hydrated, amorphous silica Pentane-2,4-dione silicon dioxide (amorphous)  2,6-dimethylheptan-4-one | 13463-67-7<br>108-65-6<br>763-69-9<br>112926-00-8<br>123-54-6<br>7631-86-9<br>108-83-8 | 15.0 mg/m3<br>6.00 MG/M3<br>0.8 mg/m3<br>150 MGM3, 25 PPM | OSHA STEL    |              |

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

**Personal Protection** 

**RESPIRATORY PROTECTION:** Respirator with filter for organic vapor.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses.

HAND PROTECTION: Solvent-resistant gloves. Follow the skin protection plan. Remove and wash contaminated clothing

before re-use. Flame retardant antistatic protective clothing

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

areas.

# 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: SILVER RESIN

Physical State Liquid

Odor ESTER-LIKE ODOR

Odor thresholdNot determinedpHNon-aqueous

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) 80 - N.D.

Flash Point, (°F / °C) 113F / 45C

Evaporation rate Not determined
Flammability (solid, gas) Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour Pressure <1 mmHg

Vapour density Not determined

Relative density Not determined

Solubility in / Miscibility with water Slight

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Viscosity

Thixotropic

Explosive properties

Not determined

9.2 Other information

Oxidising properties

VOC Content g/l: 234

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Not determined

Specific Gravity (g/cm3) 1.369

### 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions. Explosive reaction may occur on heating or burning.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Direct sources of heat.

### 10.5 Incompatible materials

Do not store together with oxidizing and self-igniting products. Strong oxidizing agents.

### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| 13463-67-7         titanium dioxide         10000 mg/kg, oral (rat)         5000 mg/kg         0.000         6,82 mg/l (rat) 4h           108-65-6         2-methoxy-1-methylethyl-acetate         5155 mg/kg, oral (rat)         >5000 mg/kg         1105 mg/m3/4H         0.000         0.000           763-69-9         ethyl 3-ethoxypropionate         3200 mg/kg Rat, oral (rat)         10 mg/24 hours rabbit         0.000         0.000           123-54-6         Pentane-2,4-dione         55 mg/kg oral, rat         10 mg/24 hours rabbit         0.000         0.000           7631-86-9         silicon dioxide (amorphous)         3,160 mg/kg, rat         58.8 mg/l, 4hr, rat, rat, inhalation         0.000         0.000           108-83-8         2,6-dimethylheptan-4-one         3200 mg/kg, oral, rat         16,000 mg/kg, rabbit         1979 ppm / 6 hrs, rat, inhalation         2000 ppm, rat hours, rat, inhalation         0.000           64742-95-6         Solvent naphtha (petroleum), light arom.         4700 mg/kg, oral, rat         >3480 mg/kg, rabbit         3670 ppm/4 hours, rat, inhalation         0.000         0.000           123-86-4         n-butyl acetate         10760 mg/kg, rat, oral         >5000 mg/kg, rabbit         23.4 mg/l/4/h (rat)         0.000         0.000   | CAS-No.    | <u>Chemical Name</u>            | Oral LD50        | Dermal LD50 | Vapor LC50    | Gas LC50      | Dust/Mist LC50 |
|--|------------|---------------------------------|------------------|-------------|---------------|---------------|----------------|
| 108-65-6   2-methoxy-1-methylenyl-acetate  | 13463-67-7 | titanium dioxide                |                  |             |               | 0.000         | ,              |
| rat 0.000 0.000 123-54-6 Pentane-2,4-dione 55 mg/kg oral, rat 10 mg/24 hours rabbit 0.000 0.000 0.000 123-54-6 Solvent naphtha (petroleum), light arom. 10760 mg/kg, >5000 mg/kg 23.4 mg/l/4/h 0.000 0.000 0.000 123-86-4 petroleum 10760 mg/kg, >5000 mg/kg 23.4 mg/l/4/h 0.000 0.0 | 108-65-6   | 2-methoxy-1-methylethyl-acetate |                  | >5000 mg/kg | 1105 mg/m3/4H | 0.000         | 0.000          |
| 7631-86-9       silicon dioxide (amorphous)       3,160 mg/kg, rat       58.8 mg/l, 4hr, rat       0.000       0.000         108-83-8       2,6-dimethylheptan-4-one       3200 mg/kg, oral, rat       16,000 mg/kg, rabbit       1979 ppm / 6 hrs, rat, inhalation       2000 ppm, rat       0.000         64742-95-6       Solvent naphtha (petroleum), light arom.       4700 mg/kg, oral, rat       >3480 mg/kg, rabbit       3670 ppm/4 hours, rat, inhalation       0.000       0.000         123-86-4       n-butyl acetate       10760 mg/kg, >5000 mg/kg       23.4 mg/l/4/h       0.000       0.000  | 763-69-9   | ethyl 3-ethoxypropionate        |                  |             |               | 0.000         | 0.000          |
| 108-83-8   2,6-dimethylheptan-4-one   3200 mg/kg, rat   rat   1979 ppm / 6 hrs, rat, inhalation   2000 ppm, rat   0.000  | 123-54-6   | Pentane-2,4-dione               |                  |             | •             | 0.000         | 0.000          |
| 108-83-8 2,6-dimethylheptan-4-one 3200 mg/kg, oral, rat rabbit 16,000 mg/kg, rabbit hrs, rat, inhalation 2000 ppm, rat 0.000  64742-95-6 Solvent naphtha (petroleum), light arom. 4700 mg/kg, oral, rat rabbit 3200 mg/kg, rabbit 3670 ppm/4 hours, rat, inhalation 0.000  123-86-4 p-butyl acetate 10760 mg/kg, >5000 mg/kg 23.4 mg/l/4/h 0.000 0.000   | 7631-86-9  | silicon dioxide (amorphous)     | 3,160 mg/kg, rat |             | • • •         | 0.000         | 0.000          |
| 64742-95-6 Solvent naphtha (petroleum), 4700 mg/kg, >3480 mg/kg, hours, rat, 0.000 0 | 108-83-8   | 2,6-dimethylheptan-4-one        |                  |             | hrs, rat,     | 2000 ppm, rat | 0.000          |
| 123-80-4   | 64742-95-6 |                                 | 0 0.             |             | hours, rat,   | 0.000         | 0.000          |
|  | 123-86-4   | n-butyl acetate                 | 0 0.             | 5 5         | •             | 0.000         | 0.000          |

### **Additional Information:**

This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

# 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB No information

assessment:

12.6 Other adverse effects: No information

| CAS-No.     | Chemical Name                            | EC50 48hr   | IC50 72hr      | LC50 96hr    |
|-------------|--|---|----------------|--------------|
| 13463-67-7  | titanium dioxide                         | >100 mg/l (EC50, 48h,<br>Daphnia magna<br>OECD202)ation | No information | >1000 mg/l   |
| 108-65-6    | 2-methoxy-1-methylethyl-acetate          | No information  | No information |              |
| 763-69-9    | ethyl 3-ethoxypropionate                 | 479.7 mg/l  | No information | 55.3 mg/l    |
| 112926-00-8 | hydrated, amorphous silica               | No information  | No information |              |
| 123-54-6    | Pentane-2,4-dione                        | No information  | No information |              |
| 7631-86-9   | silicon dioxide (amorphous)              | No information  | No information |              |
| 108-83-8    | 2,6-dimethylheptan-4-one                 | No information  | No information |              |
| 21645-51-2  | alumina trihydrate                       | No information  | No information |              |
| 64742-95-6  | Solvent naphtha (petroleum), light arom. | >1 - 10 mg/l  | >1 - 10 mg/l   | >10-100 mg/l |
| 123-86-4    | n-butyl acetate                          | No information  | No information |              |

# 13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. Dispose of as hazardous waste in compliance with local and national regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

**14.1 UN number** UN1993

**14.2 UN proper shipping name** FLAMMABLE LIQUID, N.O.S.

Technical name (CONTAINS AROMATIC HYDROCARBONS, N-BUTYL ACETATE)

14.3 Transport hazard class(es) 3

Subsidiary shipping hazard Not applicable

14.4 Packing group

 14.5
 Environmental hazards
 Not applicable

 14.6
 Special precautions for user
 Not applicable

 EmS-No.:
 F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

### **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Germ cell mutagenicity

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

 Chemical Name
 CAS-No.

 n-butyl acetate
 123-86-4

 Cumene
 98-82-8

 Benzene
 71-43-2

### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.Pentane-2.4-dione123-54-6

#### U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coating

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 234

Thinning Recommendations: The coating is to be applied without thinning.

Application Recommendations: For professional use only.

<sup>\*</sup> As per the federal EPA definition for coating categories in 40 CFR 59.401.

<sup>\*\*</sup> Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

# U.S. State Regulations: As follows -

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

polyester polyol 18275200000-5158 polyester polyol 67815-82-1

### Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

polyester polyol 18275200000-5158 polyester polyol 67815-82-1

### California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

# International Regulations: As follows -

### \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H225 | Highly flammable liquid and vapour.           |
|------|---|
| H226 | Flammable liquid and vapour.                  |
| H301 | Toxic if swallowed.                           |
| H304 | May be fatal if swallowed and enters airways. |
| H331 | Toxic if inhaled.                             |
| H335 | May cause respiratory irritation.             |
| H336 | May cause drowsiness or dizziness.            |
| H340 | May cause genetic defects.                    |
| H350 | May cause cancer                              |

### Reasons for revision

Substance and/or Product Properties Changed in Section(s):

08 - Exposure Controls/Personal Protection

11 - Toxicological Information

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.